

VEHICLE RECOVERY WINCH
EWI-10000
[Integrated]



EWI-10000

- Rated Line Pull:** 10000 lbs. (4530kgs) Single-Line
- Motor:** 6.6HP Series-Wound
- Control:** Wireless Multicontrol
- Gear Train:** 3-Stage Planetary
- Gear Ratio:** 218:1
- Clutch:** Sliding Ring Gear
- Brake:** Automatic In-The-Drum
- Drum Size:** Diameter 2.52" (64mm) Length 8.82" (224mm)
- Wire Rope:** 100', 23/64" Diameter (30m, 9.2mm Diameter)
- Fairlead:** 4-Way Roller Fairlead
- Remote Control:** Included
- Recommended Battery:** 650CCA Minimum for Winching
- Battery Leads:** 2 gauge, 72" (1.83m)
- Finish:** Dark Grey
- Weight:** 88 lbs. (40kg)
- Overall Dimensions:** (L x W x H) 21.15" x 6.3" x 10.0" (537 x 160 x 254mm)
- Mounting Bolt Pattern:** 10.00" ± 0.015" x 4.50" ± 0.010" (254.0mm x 114.3mm)

Line Speed & Amp Draw-First Layer

Line	lbs	No	2000	4000	6000	8000	10000	
Pull	kgs	Load	910	1814	2720	3630	4532	
Line	fpm	12V	28.7	16.5	12.6	9.4	8.8	6.4
Speed	Mpm	12V	8.7	5	3.8	2.9	2.7	2.0
Motor Current	Amps	12V	65	140	210	285	360	410

Line Pull & Cable Capacity

Layer of Cable		1	2	3	4
Rated Line Pull	lbs	10000	8630	7720	7090
Per Layer	kgs	4530	3910	3500	3210
Cable Capacity	ft.	16	42	72	94
Per Layer	m	5	12	21	28

Exclusive North American Distributor
T-Max, LLC
P.O. Box 4544 - Elkhart, IN 46514-0544



National Association of Testing Authorities, Australia

